

TC CURN2.2_1T aggregate unit

PRODUCT DATASHEET

TC CURN2.2_1T COOLING CHAMBER AGGREGATE UNIT

TC CURN2.2_1T in-house developed and manufactured condensing unit for cooling chamber applications. It is ideal solution for both commercial and industrial use. It can ensure efficient cooling of larger cooling rooms with an air flow capacity of 2100 m³/h, enabling rapid and precise achievement of target temperatures. Easy installation and simple maintenance ensure user-friendly operation. It is fully equipped with premium-quality Danfoss components, guaranteeing long-term performance and durability.



PRODUCT DETAILS

DIMENSIONS

Width (mm)	660
Depth (mm)	700
Height (mm)	800
Weight (kg)	71

TECHNICAL INFORMATION

Climatic class	T
Suggested refrigerant	R448A/R449A
Voltage (V)	230
Frequency (Hz)	50
Cooling capacity (W)	
[cond.45°C/evap. -10°C; R404A]	2667
Measurement standard	MBP
Application range	Refrigerating
COP (W/W)	2,32
Airflow (m ³ /h)	2100
Liquid receiver (l)	3
Shaft power (HP)	1 1/2

ELECTRICAL SPECIFICATIONS

Locked rotor amperage LRA (A)	N/A
-------------------------------	-----

PARTS

Compressor	NTU6238GKV
Condenser	UCV0316043
Fan blade diameter (mm)	350
Fan motor power (W)	69/129

ASSEMBLED FITTINGS

Pressostat HP+LP	Danfoss
Pressostat HP	Danfoss
Magnetic valve	Danfoss
Sightglass	Danfoss
Discharge filter	Danfoss
Suction filter	Danfoss

THERMOTECHNIKA-CROWN COOL KFT.

BUDAPESTI BEMUTATÓTEREM ÉS KÖZPONT: H-1103 BUDAPEST,

KÔÉR U. 3/F TELEFON: +36 1 260 7126

thermotechnika@tchungary.com

www.tchungary.com



THERMOTECHNIKA
CROWN COOL