

# TC CURN3.8\_3T aggregate unit

## PRODUCT DATASHEET

### TC CURN3.8\_3T COOLING CHAMBER AGGREGATE UNIT

TC CURN3.8\_3T in-house developed and manufactured condensing unit for cooling chamber applications. It is ideal solution for both commercial and industrial use. It can ensure efficient cooling of larger cooling rooms with an air flow capacity of 3400 m<sup>3</sup>/h, enabling rapid and precise achievement of target temperatures. Easy installation and simple maintenance ensure user-friendly operation. It is fully equipped with premium-quality Danfoss components, guaranteeing long-term performance and durability.



## PRODUCT DETAILS

### DIMENSIONS

Width (mm)	930
Depth (mm)	720
Height (mm)	850
Weight (kg)	76,5

### TECHNICAL INFORMATION

Climatic class	T
Suggested refrigerant	R448A/R449A
Voltage (V)	400
Frequency (Hz)	50
Cooling capacity (W) [cond.45°C/evap. -10°C; R404A]	3838
Measurement standard	MBP
Application range	Refrigerating
COP (W/W)	1,86
Airflow (m <sup>3</sup> /h)	3400
Liquid receiver (l)	6
Shaft power (HP)	2

### ELECTRICAL SPECIFICATIONS

Locked rotor amperage LRA (A)	22
-------------------------------	----

### PARTS

Compressor	NJX6250GS
Condenser	UCV0320063
Fan blade diameter (mm)	400
Fan motor power (W)	112/180

### ASSEMBLED FITTINGS

Pressostat HP+LP	Danfoss
Pressostat HP	Danfoss
Magnetic valve	Danfoss
Sightglass	Danfoss
Discharge filter	Danfoss
Suction filter	Danfoss

## THERMOTECHNIKA-CROWN COOL KFT.

BUDAPESTI BEMUTATÓTEREM ÉS KÖZPONT: H-1103 BUDAPEST,

KÔÉR U. 3/F TELEFON: +36 1 260 7126

thermotechnika@tchungary.com

[www.tchungary.com](http://www.tchungary.com)



**THERMOTECHNIKA  
CROWN COOL**